

PACKLOG

FIXED – ADJUSTABLE HEIGHT WITH ADJUSTABLE BRACKETS



ERGONOMICS - MULTI-USES - FUNCTIONALITY

FIXED FRAME PACKLOG – CHARACTERISTICS OF THE METAL STRUCTURE



PACKLOG fixed frame

The frame consists of a structure of tubular steel thickness 20/10 and formed sheet thickness 25/10.

The legs are made from 40x40mm section welded tube, the horizontal cross members formed in to an U section 40x60x40mm.




The 3 cross members join the ladders :

- 2 under the worktop
- 1 on the table's back
- A back panel between the 2 shaped legs is fixed to the top back of the frame

The framework is finished in epoxy powder paint polymerized in a kiln at 180.

Come with 4 plastic foot covers to protect the floor.



Structure and worktop association

The structure can be associated with 24MM & 40MM Mutiplex worktop with galva coating or PEHD coating, with Laminated RESITOP 30MM worktop or 19&28MM melamine-coated worktop.

The worktop is fixed to the structure by a VBA TB 5x20 screw.



Workbenches dimensions

- Height: 900 mm (excl. worktop)
- Depths : 750 or 1000 mm
- Lengths : 1200, 1500, 1800, 2000 or 2400 mm



Assembly

- Fast and easy assembly
- Delivered as a kit
- Can be assembled on request

CERTIFICATION

The worktops are PEFC certified
The fixed frame can bear up to 500Kgs
In compliance with NF XPD 65762





PACKLOG WITH HEIGHT ADJUSTABLE FRAME – CHARACTERISTICS OF THE METAL STRUCTURE



PACKLOG frame with adjustable height with adjustable brackets

The frame consists of a structure of tubular steel thickness 20/10 and formed sheet thickness 25/10.

The legs are made from 40x40mm section welded tube, the horizontal cross members formed in to an U section 40x60x40mm.

The 3 cross members join the ladders :

- 2 under the worktop
- 1 on the table's back
- A back panel between the 2 shaped legs is fixed to the top back of the frame



The framework is finished in epoxy powder paint polymerized in a kiln at 180. The sliding and clamping system with 4 screws does not require any dismantling.

Notches located every 20mm enable to adjust the height and to have a reference mark. The height can be adjusted from 740 to 1020 mm (excl. worktop's thickness).



Structure and worktop association

The structure can be associated with 24MM & 40MM Multiplex worktop with galva coating or PEHD coating, with Laminated RESITOP 30MM worktop or 19&28MM melamine-coated worktop.

The worktop is fixed to the structure by a VBA TB 5x20 screw.



Workbenches dimensions

- Height : 740 to 1020 mm (excl. worktop)
- Depths : 750 or 1000 mm
- Lengths: 1200, 1500, 1800, 2000 or 2400 mm



Assembly

- Fast and easy assembly
- Delivered as a kit
- Can be assembled on request

CERTIFICATION

The worktops are PEFC certified

The height adjustable frame can bear up to 300Kgs

In compliance with NF XPD 65762





ACCESSORIES



PACKLOG UPRIGHTS FOR SUPERSTRUCTURE

H. 600mm : for 2 or 3 uprights
H. 1200 mm : for 2 or 3 uprights



RAIL FOR CONTAINER

To be fixed between the 2 superstructure uprights

L. 635 / 865 / 1300 mm



PERFORATED TAPE

To be fixed between the 2 superstructure uprights

L. 635 / 865 / 1300 mm



EDGE SHELF

To be fixed to an upright, a rail for container or a perforated panel

L. 200 / 340 / 510 mm - D. 220 mm



MULTIFUNCTIONS EDGE SHELVES

To be fixed to an upright, a rail for container or a perforated panel

L. 330 mm - D. 240 mm



TROUGH SHELF

To be fixed between the 2 superstructure uprights

L. 635 / 865 / 1300 mm



DISPENSER BAR

To be fixed between the 2 superstructure uprights

For rolls of bubble wrap, kraft paper or corrugated paper

L. 635 / 865 / 1300 mm - Diam. 25 mm



DOUBLE LABELS DISPENSER

To be fixed to an upright, a rail for container or a perforated panel

L. 150 mm on each side - Diam. 25 mm



LABELS DISPENSER

To be fixed on an upright

L. 360 mm - Diam 30 mm



UNDER-WORKSTATION DISPENSER BAR

For rolls of bubble wrap, kraft paper or corrugated paper;
Rolls with diam. maxi 800 mm on fixed PACKLOG and maxi 500mm on adjustable PACKLOG

L. 875 / 1310 / 1650 mm



TILTING AND DEPTH ADJUSTABLE SHELF

To be fixed between the superstructure uprights

L. 635 / 865 / 1300 mm - D. 250 mm
L. 635 / 865 / 1300 mm - D. 350 mm
L. 635 / 865 / 1300 mm - D. 450 mm



TILTING SHELF

To be fixed between the superstructure uprights

L. 865 / 1300 mm - D. 250 mm
L. 865 / 1300 mm - D. 350 mm
L. 865 / 1300 mm - D. 450 mm



SLIDING SUPPORT FOR ZEBRA PRINTER

The drawer support comes with a 100% opening for a full access to the printer

L. 427 mm - D. 588 mm - H. 350 mm



MANUAL PAPER CUTTER

To be fixed on or under the worktop or between the uprights

Guided line for the cutter, system to hold the cutted paper

Locking system in open position
L. 865 / 1300 / 1760 mm



25L BIN WITH ITS HANGING SYSTEM

To be fixed to the ladders or under the worktop

L. 340 mm - D. 258 mm - H. 344 mm



SHELF WITH SEPARATORS

The separators are fixed under the shelf by screws and nuts each 120 or 125MM (according to the shelf's dimensions)

L. 635 / 865 / 1300 / 1760 mm - H. 350 mm - D. 500 mm



SET OF 6 SEPARATORS

Fixing system on the shelf by screws and nuts

H. 350 mm - D. 500 mm



BOX AND DRAWERS

100% pull-out drawers

Box : L. 427 mm - D. 589 mm - H. 125 mm
Drawers : L. 396 mm - D. 5602 mm - H. 120 mm
Usless dimensions

ACCESSORIES



ROLLING HORIZONTAL DISPENSER BAR

With or without cutting bar

For rolls of bubble wrap, kraft paper or corrugated paper

L. 865 / 1300 / 1760 mm H785mm - D885mm



KIT OF DISPENSER BAR

For rolling horizontal dispenser bar


Guided line for the cutter, system to hold the cutted paper



ROLLING VERTICAL DISPENSER BAR

Guided line for the cutter, system to hold the cutted paper

Locking system in open position



ACCESSORIES FOR TOOLS HOLDER

For perforated panel



PERFORATED PANEL

To be fixed between the superstructure uprights

L. 635 / 865 / 1300 mm - H. 375 mm



MAGNETIC PANEL

To be fixed between the superstructure uprights

L. 635 / 865 / 1300 mm - H. 450 mm



ELECTRICAL STRIP WITH SWITCH

To be fixed between the superstructure uprights or on the worktop

L. 440 mm



LED LIGHTING STRIP

15W with switch

L. 810 mm - D. 80 mm
H. 50 mm



10 A4 TRANSPARENT POCKETS WITH HOLDER

10 transparent pockets with coloured borders to be fixed on a metal support



BOTTLE HOLDER

L. 100 mm - D. 100 mm
H. 130 mm



BOTTLES HOLDER

L. 630 mm - D.110 mm
H. 120 mm



KEYBOARD AND MOUSE HOLDER

L. 585 mm - D. 330 mm - H. 80 mm



ADJUSTABLE AND SECURED SUPPORT FOR CENTRAL PROCESSING UNIT

Vertical fixation under the worktop

L. 140/190 mm - D. 350/498 mm ; D. 464 mm useless dimensions



CENTRAL PROCESSING UNIT FIXATION

For superstructure uprights

L. 100 mm - D.225 mm - H.250 mm



SWIVELLING TABLE ON ARTICULATED ARM

To be fixed on one of the superstructure uprights

For Europe box or laptop



FIXING SYSTEM FOR 27" MAX SCREEN

To be fixed between the superstructure uprights



FIXING SYSTEM FOR 10/12" PADS



LAPTOP FIXING SYSTEM

L. 500 mm - D. 250 mm



LAPTOP FIXING SYSTEM

L. 550 mm - D. 250 mm

To be fixed on one of the superstructure uprights



DRAWERS UNIT

From 1 to 6 drawers

L. 430 mm - D.600 mm - H. 100 / 380 / 530 mm



DOOR UNIT

L. 430 / 860 mm - D.600 mm - H. 530 mm



SET OF 4 CASTORS

Set of 4 castors diam 100 mm
Incl. 2 breakable castors

STRENGTHS OF THE PACKLOG RANGE

FIXED - ADJUSTABLE HEIGHT BY ADJUSTABLE BRACKETS


ERGONOMICS



MULTI-USES



FUNCTIONALITY



PACKLOG WORKBENCH STANDARD COLOURS



RAL 1015 BS



RAL 1018 JS



RAL 2004 OG




RAL 3000 RV



RAL 5002 BM




RAL 5010 BP




RAL 5015 BI



RAL 7004 GM



RAL 7016 GA



RAL 7035 GC



RAL 9005 NN



RAL 9010 BB



RAL 7035 ESD

Colours to be defined : frame

STANDARD WORKTOP COATINGS



LIGHT GRAY MELAMINE & LAMINATED



BEECH MULTIPLEX



MARBLED BLUE SOUPLÉDUR



WHITE PEHD



BLACK RUBBER



GALVA



INOX



WARRANTY :

Our equipment is guaranteed 5 years under normal use



FRENCH MANUFACTURER

SOFAME
The industrial furniture experts

www.sofame.fr